




Scanbody QR,  
indexed – narrow  
Ref. No. 2876.00



Connection type

QR/I 

QR/NI 

QR/B 

Application

Solo crown

Linear bridge

Bridge








#### Free library

exocad\_BioniQ\_Uni-Base.zip

Ref. No. 2858.00



S3.5  
S4.0  
T4.0  
S5.0  
T5.0


Specification		L0.7	L1.5	L2.5	Compatible burn-out coping
QR/I/d4.5/h5.5		2218.07	2218.15	2218.25	2879.00
QR/I/d4.5/h8.0		2225.07		2225.25	2879.00
QR/I/d4.5/h3.5			2230.15		2879.00
QR/I/d3.8/h5.5		2216.07	2216.15		2878.00
QR/NI/d4.5/h5.5			2220.15		2879.00
QR/B/d4.5/h5.5		2221.07			2879.00
QR/B/d4.5/h3.5			2234.15		2879.00

LASAK BioniQ QN Exocad library structure

**exocad\_BioniQ\_Uni-Base.zip**



Scanbody QN,  
indexed – narrow  
Ref. No. 2877.00



Connection type

QN/I

Application

Solo crown

Free library

**exocad\_BioniQ\_Uni-Base.zip**

Ref. No. 2859.00



S2.9

Specification

QN/I/d3.8/h5.5



L0.7

2208.7

L1.5

2208.15

L2.5

Compatible  
burn-out coping

2878.00